

MISSION DATA CARD						
OPORD		Callsign		Mission		Date/Time
1979/2023		Edelweiss 6		Training		122000JUN23
Task	Tactical Formation					Freq
AO	R66					134.65
Departure				Recovery		
FYTTR LOW				STRYK		
#	Callsign	Pilot		IFF	TCN	LSR NET
-1	Edelweiss 6-1	G-Rex		1761	21Y	1661 40/01
-2	Edelweiss 6-2	addiks		1762	84Y	1662 40/02

LOADOUT			
A/A	A9M		GUN 100% CM
A/G	7M282L		CHF 120
POD	A184, TGP		FLR 360
TKS			FUEL 100%

TOLD					
	Takeoff	Target	Joker	Bingo	Land
FUEL	11087				

AIRBASES								
	Name	TCN	ATIS	GND	TWR	RWY	Elev	ILS
Dep	Nellis AFB	12X	270.1	275.8	327.0	21L	1850	109.1
Arr	Nellis AFB	12X	270.1	275.8	327.0	21L	1850	109.1
Div	Creech AFB	87X	290.45	275.8	360.6			

FLIGHTPLAN				
#	Name	Navaid/Coords/DME	ALT	TOT
1	Nellis	N36 14.680 W115 01.500		
2	FYTTR	LSV 269/33 (N36 21.440 W115 41.470)	11000	
3	T66.01	N35 34.881 W116 42.391	11000	
4	STRYK	LSV 282/26 (N36 25.620 W115 30.700)	9500	
5	GASS PEAK	LSV 309/12 (N36 24.140 W115 10.660)	8500	
6	SIMNS	LSV 276/8 (N36 17.340 W115 10.750)	5500	
7	Nellis	N36 14.680 W115 01.500		

COMMS	
Radio	Usage
1	134.65
2	11-3-4-16-11-4-3

NOTES

Defensive Combat Spread
Tac turn
Shackle
In place
Cross turn

OTHER FLIGHTS						
Callsign	Mission	Airframe	Freq	TCN	Grpld	Laser
Outlaw* 1	Training	2x AH-64D	133.5	21/84		156X
	AO	Range 75	Task	Recon, Hellfire		
Raptor 1	Training	4x F-16C	134.0	21/84		156X
	AO	BFM RangeZ	Task	Fox2 Training		
T-Rex 2	Training	2x A-10C	132.0	21/84	25	156X
	AO	R66	Task	Tactical Formation		

RADIO CHANNELS		
#	Freq	Name
1		Flight/Squadron specific
2	289.4	Nellis Clearance Delivery
3	275.8	Nellis Ground
4	327.0	Nellis Tower
5	385.4	Nellis Approach/Departure West
6	273.55	Nellis Approach/Departure East
7	317.525	Nellis Control -- Sally
8	254.4	Nellis Control-- Lee
9	305.6	SOF Bullseye
10	343.725	EMERGENCY SINGLE FRQ
11	270.1	Nellis ATIS
12	360.625	Creech AFB Tower
13	250.1	HAVE QUICK 13
14	251.1	HAVE QUICK 14
15	252.1	HAVE QUICK 15
16	377.8	Blackjack
17	265.0	KC-135 AR-641A
18	360.8	KC-135MPRS AR-635
19	319.8	KC-135MPRS AR-625
20	300.05	KC-135 AR-231V

RAMROD										
0	1	2	3	4	5	6	7	8	9	
D	U	P	L	I	C	A	T	E	S	
KTC 1400 C										
	0	1	2	3	4	5	6	7	8	9
A	CTYK	DWI	AHS	BG	EP	FVN	MX	RJ	QO	UL
B	RBIU	WQX	JGM	DO	HS	FNY	AC	LK	VT	PE
C	NHRP	MXE	FSD	QG	UW	ABV	YK	OJ	LT	CI
D	ORQS	TYC	MHV	BI	LA	NFX	PU	DK	JG	EW
E	CNWS	OUQ	GKI	TV	HM	BAX	PJ	FD	RL	YE
F	YXPV	IEQ	LHU	AW	DC	TMJ	KG	BS	NR	FO
G	XVLU	PHN	TJR	KA	BS	FQE	OC	IW	DG	YM
H	CXSW	ARQ	NHE	GY	VM	TJK	OB	UI	DL	PF
I	MESK	AGJ	NXI	TP	QV	RLY	FD	BH	OC	WU
J	KLGJ	FDR	WBP	TA	CN	QSM	YV	EO	XI	UH
K	EXPS	GHQ	IWK	FU	RB	NYV	LM	OA	TD	JC
L	OUKT	NRP	GED	YH	CM	AIJ	FV	BX	SW	QL
M	XHUP	BRO	DLW	IJ	KV	YQN	AE	TM	FS	GC
N	VSIL	YJK	XFB	OR	GU	WHC	PE	DM	AQ	TN
O	PEIV	FKG	XUW	LC	AY	QHM	OT	DN	RB	JS
P	RPUC	GWT	QJV	EK	LX	SBF	MD	OY	AN	IH
Q	OQDY	ABK	XIN	MS	TF	LCP	WG	UJ	RE	VH
R	NOIP	JGC	LBR	QY	DV	KXS	FU	MH	WE	AT
S	RNIA	PBY	FGL	OW	XQ	VEU	DS	KM	CT	HJ
T	CSQP	UOH	RDW	XG	EB	TJF	LN	VI	YA	MK
U	UIJM	VFB	TAP	XR	LO	ESN	KQ	DC	GH	YW
V	PGWA	UQK	HRL	EM	CY	FXJ	SN	ID	BT	OV
W	DUPN	CYV	KEA	BF	RX	WGI	JS	ML	TQ	OH
X	FTRK	DLS	QPJ	GN	CY	HOA	UX	EM	VW	BI
Y	IFOD	SHV	KPW	EJ	XY	BGC	TR	NM	AU	QL

NAVAIDS				
Id	Name	Channel	Position	Elevation
BCE	Bryce Canyon	75	N3741.35 W11218.23	9040
BIH	Bishop	33	N3722.62 W11821.99	4114
BLD	Boulder	114	N3559.75 W11451.82	3650
BTY	Beatty	94	N3648.54 W11644.86	2925
CDC	Cedar City	120	N3747.24 W11304.90	5463
DAG	Daggett	79	N3457.75 W11634.69	1760
EED	Needles	99	N3445.96 W11428.43	650
GFS	Goffs	91	N3507.87 W11510.59	4019
GRL	Groom Lake	18	N3713.91 W11548.16	4475
HEC	Hector	74	N3447.83 W11627.78	1854
ILC	Wilson Creek	110	N3815.02 W11423.65	9318
INS	Creech AFB	87	N3635.20 W11540.12	3101
LAS	McCarran Intl	116	N3604.78 W11509.59	2142
LSV	Nellis	12	N3614.68 W11501.50	1864
MLF	Milford	58	N3821.62 W11300.79	4977
MMM	Mormon Mesa	90	N3646.16 W11416.65	2120
MVA	Mina	98	N3833.92 W11801.97	7860
OAL	Coale Dale	124	N3800.20 W11746.23	4800
PGS	Peach Springs	57	N3537.48 W11332.67	4754
TPH	Tonopah Muni	119	N3801.84 W11702.01	5330
TQQ	Silverbow	77	N3748.00 W11647.00	5500
UTI	St George	23	N3705.29 W11335.53	2871



PAR	RWY	CAT	MINIMA	ARP	ELEV	Scale 1:35'500
	21L	A B D E	2057 - 0.8 200 (200-0.8/1.6) GS 3°	36° 14.060° N	1857 [ft]	0 300 600 900 1200 1500 [m]
	3R	A B D E	2057 - 0.8 200 (200-0.8/1.6) GS 3°	115° 01.058° W	566 [m]	0 1000 2000 3000 4000 5000 [ft]
SRA	RWY	CAT	MINIMA	ARP	ELEV	Scale 1:35'500
	21R	A C D E	2257 - 1.2 350 (350-1.2/1.6)	36° 14.060° N	1857 [ft]	0 300 600 900 1200 1500 [m]
	3L	A C D E	2257 - 1.2 350 (350-1.2/1.6)	115° 01.058° W	566 [m]	0 1000 2000 3000 4000 5000 [ft]

RWY	TORA	TODA	ASDA	LDA	PSN THR	ALS
21L	10051 [ft] 3063 [m]	11051 [ft] 3368 [m]	11051 [ft] 3368 [m]	10051 [ft] 3063 [m]	36°14.043°N 115°01.018°W	⊕
3R	10120 [ft] 3084 [m]	11120 [ft] 3398 [m]	11120 [ft] 3398 [m]	10120 [ft] 3084 [m]	36°13.029°N 115°02.038°W	

ATIS	NELLIS GROUND	NELLIS TOWER	NELLIS CONTROL	TACAN	ILS RWY 21L	NELLIS EAST	NELLIS WEST
270.100 MHz	275.800 121.800	327.000 132.55	317.525	LSV 12X	109.10 Mhz	384.400	385.000


ATIS
 270.100
 NELLIS GROUND
 275.800
 NELLIS TOWER
 327.000
 NELLIS CONTROL
 317.525
 NELLIS DEP/APP EAST
 384.400
 BLACKJACK
 377.800

CAUTION: If unable to comply
with restrictions advise ATC
prior to departure.

VMC ONLY

PILOT RESPONSIBLE FOR TERRAIN AVOIDANCE

① 4 NM from RWY 3L/R



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 3L/R:

- Remain below 3,000' MSL until north of Race Track and turned westbound.
- Turn left within 4NM of Nellis direct FLEX. Fly north of FLEX and turn left heading 270°.
- Intercept LSV R-255 between 5,000' and 6,000' , intercept and proceed outbound on the LSV R-269. Recommend climb to 8,500' MSL or appropriate VFR altitude for overflight of North Las Vegas Training Area. Fly routing for appr. mission/transition.
- ARC south, intercept LSV R-269 outbound. Maintain VFR.

TAKEOFF RWY 21L/21R:

- Follow Noise Abatement Procedures.
- Fly runway heading until past Golf Course, turn right heading 300°.
- Cross LSV R-255 between 5,000' and 6,000' , intercept and proceed outbound on the LSV R-269. Recommend climb to 8,500' MSL or appropriate VFR altitude for overflight of North Las Vegas Training Area. Fly routing for appr. mission/transition.

TRANSITIONS:

R-4806: Turn right at the LSV 269/20 direct to assigned ranges.

BEATTY: Turn right at FYTTR direct BTY via the BTY R-105

R-2508: Turn right at the FYTTR, intercept the BTY 105/30, direct TUCKY, then direct R-2508

FYTTR DEPARTURE AND TRANSITIONS (FYTTR LOW)



APPROACH ROUTE DESCRIPTION

APPROACH RWY 3L/R

Cross STRYK at or above 9,500' MSL, proceed direct GASS PEAK. Cross JORDN at or above 9,500' MSL, cross GASS PEAK at or above 8,500' MSL. Proceed direct SIMNS and cross at 5,500' MSL. Cross Las Vegas Blvd at or above 4,000' MSL then to 3,500' MSL for Initial. Remain within 4 DME if LSV on turn to final.

VFR STRAIGHT-IN RWY 3L/R

Depart CRAIG & descend to be at 3,000' MSL by Las Vegas Blvd. Do not descend below 3,000' MSL until within 5 DME of LSV or 4 NM of the runway on turn to final.

APPROACH RWY 21L/R

Cross STRYK at or above 9,500' MSL, proceed direct GASS PEAK. Cross JORDN at or above 9,500' MSL, cross GASS PEAK at or above 8,500' MSL. Cross APEX at or above 4,500' MSL then direct 5NM initial. Descend to cross PHINN at 4,000' MSL, Inside 5 NM descend to 3,500' MSL.

VFR STRAIGHT-IN RWY 21L/R

Cross APEX at 4,000' MSL. Descend to be at 3,000' MSL at PHINN. Descend to 3,000' MSL at LSV 027/5.

RANGE 63B EXIT

SOUTH: Via NIXON at or above 10,000' MSL, then direct STRYK.

EAST: Via SARAH at or above 10,000' MSL, then direct GASS PEAK.



INDIAN SPRINGS, NEVADA

TACAN INS Chan 87	APCH CRS 065 °	Rwy ldg TDZE Arpt Elev	9002 3133 3113
----------------------	-------------------	------------------------------	----------------------

INDIAN SPRINGS AF AUX (KINS)



* MISSED APPROACH: Straight ahead to INS TACAN, intercept INS R-outbound, cross 17 DME at or above 9500, then direkt KSV TACAN

114

NELLIS CON

CREECH AFB TOWER
118.30 660.60

GND CON


NOT FOR CIVIL USE

FOR USE UNDER BASIC VFR
WEATHER MINIMUMS ONLY

PILOT IS RESPONSIBLE FOR TERRAIN/OBSTACLE
AVOIDANCE AND
APPROPRIATE VFR CLOUD
CLEARANCE FOR ALL

CAUTION: Descent gradients
are greater than allowed under standard
TERPS criteria and inbound course
does not meet straight-in criteria


CAUTION: Final approach course crosses
Runway centerline at MIDFIELD. Maneuvering
left of course required prior to landing. Do not
Maneuver farther north than the INS R- 258



* CAUTION: Missed Approach Climb Rate to 4,700


Knots	60	120	180	240	300
V/V (fpm)	230	460	690	920	1150

Controlling Obstacle



HIGH ALTITUDE FACILITIES

EMERG SAFE ALT 100 NM 14,000



CATEGORY	A	B	C	D	E
S-8	3760-1 ½	627 (700-1 ½)	3760-1¾ 627 (700-1¾)	3760-2 627 (700-2)	3760-2¼ 627 (700-2¼)
CIRCLING	NOT AUTHORIZED				

MIRL Rwy 8-26

CITY OF INDIAN, NEVADA

INDIAN SPRINGS AF AUX (KINS)

(FOR DAY VFR USE ONLY)

Modified by vJaBoG 66 for use with DCS
NOT FOR REAL LIFE NAVIGATION



